

**Amendments to the Claims:**

This listing will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Currently amended) A thermoplastic polyolefin (TPO) roofing membrane comprising a reinforcement scrim sandwiched between cap and base layers which are pressed into a single ply membrane having a thickness of about 35-90 mils, characterized in that both of said layers are made of, by weight, 50-90% of metallocene-catalyzed polyolefin, and about 10-50% of additives including a crystallinity enhancing polymer comprising high density polyethylene (HDPE), said membrane exhibiting a 90° heat seam peel strength of  $\geq 60$  lbs/linear inch (ASTM D-413) and a cold brittleness point of  $\leq -50^{\circ}\text{C}$  (ASTM D-413).

2. (Original) A roofing membrane according to claim 1 wherein said 90° heat seam peel strength is about 66-69 lbs/linear inch over a 4 day period, and said cold brittleness point is about  $-58$  to  $-70^{\circ}\text{C}$ .

3. (Original) A roofing membrane according to claim 1 wherein said polyolefin is a copolymer of ethylene and butane.

4. (Canceled)

5. (Original) A roofing membrane according to claim 1 wherein the molecular weight distribution (MWD) of said polyolefin is about 2 to 2.5.